

Freeman Roofing Alpine Tray	
0.4mm	Colorsteel® Maxam®
0.55mm	Colorsteel® Maxam®
0.4mm	Zincalume®
0.55mm	Zincalume®

Ridge/Hip flashing BMT to match Alpine Tray material

Under flashing BMT to match Alpine Tray material

TRAY stop end

Treated timber batten

Timber rafter

Vapour barrier/ Roofing Underlay to underside of tray cladding

Notes:  
 Category A:  
 Low, Medium or High Wind Zones, all pitches  
 Very High and Extra High Wind Zones where the pitch is equal to or greater than 10°.

Category B:  
 Very High where the pitch is less than 8°, and  
 Extra High Wind Zones all pitches.

Category C:  
 SED Wind Zones up to 60 m/s all pitches.

Category D:  
 SED up to 68 m/s, all pitches.

Category				
Dimension	A	B	C	D
C1	130 mm	200 mm	200 mm	200mm + baffle
Ridge Type	STD	Wide	Wide	Wide
Purlin Position X				
Pitch 8°-15°	165 mm	150 mm	150 mm	150 mm
Pitch 15°-30°	150 mm	200 mm	200 mm	200 mm
Pitch 30°-45°	130 mm	180 mm	180 mm	180 mm